

Performance Analysis of MIMO-STBC using Hamming Channel Codes for different modulation techniques

Khushboo Bisht¹, Parminder Singh², Dr. Sanjay Sharma³

¹(Mtech Student, ECE Department, DIET, Kharar, Mohali)

²(AP, ECE Department, Diet, Kharar, Mohali)

³(H.O.D., Thapar University, Patiala)

Abstract: MIMO Diversity is a technique to mitigate the effect of fading and enhances the signal strength. STBC is used in MIMO systems to improve the performance by maximizing the diversity gain. In this paper, performance of MIMO-STBC for different modulation techniques such as BPSK, QPSK, 8-PSK and 16-PSK using Hamming Coding is analysed on the basis of BER and SNR. A comparative study and performance analysis is done for SISO, SIMO, MISO and MIMO systems for BPSK modulation technique.

Keywords: Multiple- input Multiple-output (MIMO), Space Time Block Code(STBC), Alamouti, Bit Error Rate(BER), Hamming Coding .

I. Introduction

Wireless systems are rapidly developing to provide high speed data transfer but the major problem is data rate and range. To support these services large capacity channels are required. In wireless communication, the signal from transmitter is reached from various paths due to reflection, refraction, diffraction etc. Each path experiences different time delay, phase shift and attenuation which results in fluctuation in signal strength. This is known as multipath fading. As a result of fading multiple copies of transmitted signal is received at the receiver which degrades the system performance [1]. The basic idea is that if different copies of same signal are available then there is a high probability that at least one of them is of good quality [2]. To improve the performance in fading channels diversity technique is used. We transmit different copies of signal through different channels instead of transmitting them over one channel. Diversity can be obtained by using multiple antennas both at transmitter and receiver end. This system is called multiple-input multiple-output (MIMO). These systems got higher consideration in Alamouti STBC where data is coded through space and time [3]. MIMO is based on both transmit and receive diversity. The overall effect MIMO systems can be summarized in terms of reduction of bit error rate and increase in system capacity [4]. This paper describes a wireless transmission using the concept of MIMO systems. MIMO using Space Time Block Coding (STBC) has been used with different modulation techniques such as BPSK, QPSK, 8-PSK and 16-PSK using hamming coding. This technique is capable of providing better data rates and significant reduction in bit error rate.

II. Space Time Block Code

Space time block code is presented by the Alamouti [5]. This scheme provides transmit and receive diversity to the MIMO systems. A simplified block diagram using Alamouti is described in fig.1. This scheme is defined by following three functions:

1. Encoding and decoding transmission sequence information symbols at the transmitter.
2. Combining signals with noise at the receiver.
3. Maximum likelihood detection.




Fig.1. Simplified Alamouti space time coding (STC) for 2x2 MIMO systems [5].

At a given time period, two signals are simultaneously transmitted from two antennas. At time t , antenna 0 will transmit the signal S_0 and antenna 1 will transmit the signal S_1 . At time $(t+T)$, antenna 0 will transmit the signal $(-S_1^*)$ and antenna 1 will transmit the signal S_0^* where $*$ is complex conjugate operation. The sequence is shown below:

Table 1. Encoding and transmission sequence for Alamouti STBC scheme [5]

Time	Slots	Antenna 0	Antenna 1
time t		S_0	S_1
time $(t+T)$		$(-S_1^*)$	S_0^*

The received vectors can be expressed as,

$$r_0 = h_0 S_0 + h_1 S_1 + n_0 \quad (1)$$

$$r_1 = h_0 (-S_1^*) + h_1 S_0^* + n_1 \quad (2)$$

$$r_2 = h_2 S_0 + h_3 S_1 + n_2 \quad (3)$$

$$r_3 = h_2 (-S_1^*) + h_3 S_0^* + n_3 \quad (4)$$

where n_0, n_1, n_2, n_3 are thermal noise and interference, r_0, r_1, r_2, r_3 denote the received vectors and S_0 and S_1 are modulated symbols.

The combiner will combine the two signals and then are sent to the maximum likelihood detector and expressed as,

$$\tilde{S}_0 = h_0^* r_0 + h_1 r_1^* + h_2^* r_2 + h_3 r_3^* \quad (5)$$

$$\tilde{S}_1 = h_1^* r_0 - h_0 r_1^* + h_3^* r_2 - h_2 r_3^* \quad (6)$$

III. System Model

The system model is shown in fig.2. At first the data bits are transmitted through Rayleigh Fading channel. The channel encoder adds the redundant bits to the information pattern for error detection and correction. These data streams are modulated using M-PSK techniques. The signal is passed through Space Time Block Coder (STBC). Now all the modulated streams travel through the channel and then first decoded by STBC decoder and demodulated by M-PSK demodulator and then channel demodulator to get the received signal.




Fig.2. System Model [1]

3.1 Transmitter

The data is generated from random source, consists of series of zeroes and ones. The data is passed to next stage.

3.1.1 CHANNEL ENCODER

The Channel Encoder adds the redundant bits to the data bits for error correction and detection. In this model, hamming coding is used as a channel encoding technique. Hamming introduced the (7,4) code. It encodes 4 data bits into 7 bits by adding three parity bits. Hamming (7,4) can detect and correct single-bit errors.

3.1.2 MODULATION

The incoming data streams are modulated by using M-PSK techniques. There are four modulation techniques that are BPSK, QPSK, 8-PSK, and 16-PSK.

3.1.3 STBC ENCODER

Space Time Block Coding (STBC) based on Alamouti scheme based on both transmit and receive diversity [5]. S_0 and S_1 are the actual transmitted signal. The signal is passed through Rayleigh flat fading channel.

3.1.4 STBC DECODER

In the STBC decoder received signals are combined by maximal ratio combining and detected by maximum likelihood detection.

3.1.5 DEMODULATOR

Demodulator converts the modulated waveform created at the receiver to their original bits.

3.1.6 CHANNEL DECODER

At the receiver, channel decoding is done using syndrome decoding.

IV. Simulation Results




Fig.3 BER Plot of STBC for SISO system using BPSK




Fig.4 BER Plot of STBC for SIMO system using BPSK




Fig.5 BER Plot of STBC for MISO system using BPSK




Fig.6 BER Plot of STBC for MIMO system using BPSK without channel coding




Fig.7 BER Plot of MIMO-STBC for BPSK, QPSK, 8-PSK, 16-PSK using Hamming Coding

In the simulation, the channel is assumed to be Rayleigh flat fading channel. The transmission employs different modulation techniques such as BPSK, QPSK, 8-PSK and 16-PSK. Maximum likelihood detection is done at the receiver for detection of signal. BPSK is more power efficient and needs less bandwidth. BPSK has less BER than the other techniques.

Table 2. SNR required at BER 5×10^{-2} for M-PSK for 2*2 Alamouti Scheme with Hamming Coding

Sr. No.	Modulation Scheme	SNR(db)
1	BPSK	1.2
2	QPSK	5.3
3	8-PSK	10.8
4	16-PSK	16.5

V. Conclusion

Space Time Block Codes with low order modulation always give low bit error rate as compared with Space Time Block Code with high order modulation. The result shows that Bit Error Rate (BER) of STBC with 16-PSK modulation is less for high SNR and BER with BPSK is less for low SNR. Thus STBC with BPSK is more power efficient and require less bandwidth.

References

- [1]. Roshan Kumar, "Performance Analysis of STBC with channel coding", Thapar University, Patiala ,Punjab,2010.
- [2]. Hafeth Hourani, "An overview of diversity techniques in wireless communication system", Helsinki University of Technology communication lab, 2004-05.
- [3]. Bhawna Ahlawat and R.K.Reddy,"Channel Estimation and Performance Evaluation of STBC with channel coding", International Journal of Engineering Research and Technology (IJERT), vol.1, issue 3, 2012.
- [4]. Shubhangi Chaudhary and A.J.Patil, "Performance Analysis of MIMO STBC with different modulation techniques", ICTACT Journal on communication and technology, vol.03, issue 01, 2012.
- [5]. S.M.Alamouti, "A simple transmitter diversity technique for wireless communications", IEEE Journal on selected areas communication, vol.16, No.8, pp.1451-1458,1998.